

# Anti Slip

6 COLOURS | 9 FINISHES | 6 SIZES



Floor:  
2SCT3086

Project:  
North Devon Leisure Centre

# Anti Slip


These specialist tiles are suited to areas requiring excellent anti slip properties. Due to the wide range of colours, sizes and finishes, please call our sales team for assistance with this complex range.



## ANTI SLIP FINISHES



Abete Finish  
R12 V8 (A+B+C)



Apol Finish  
R13 (A+B+C)



Bosso Finish  
R12 V4 (A+B+C)



Ebano Finish  
R11 (A+B)



Jennet Finish  
R10



Lyrid Finish  
R11 V6 (A+B+C)



Milon Finish  
R12



Palude Finish  
R11 (A+B)



Pesse Finish  
R11 V4 (A+B+C)

## PORCELAIN SOLID BASICS COLOURS



Salt  
2SCT1018



Sambal  
2SCT1019



Punch  
2SCT1015

## PORCELAIN FLARE COLOURS



Nebulosa  
2SCT3081



Actina  
2SCT3085



Canuk  
2SCT3086

## NOTES






Please see Porcelain Solid Basics range for additional sizes and colours in a Matt R9 and Polished finish.  
Please see Porcelain Flare range for additional sizes and colours in a Matt R9 and Polished finish.

## SIZES AND FINISHES




	200x200 8mm	200x200 12mm	200x200 14mm	300x300 8mm	300x300 11.2mm	300x300 14mm
Salt	●▲◆♥□○\	●▲◆♥□○\	●▲◆♥□○	▲◆□	▲◆□	▲◆□
Sambal	●△◆♥■□○	●△◆♥■□○	●△◆♥□○	▲◆□	▲◆□	▲◆□
Punch	●▲◆♥□○	●▲◆♥□○	●▲◆♥□○	▲□	▲◆□	▲□
Nebulosa	●△◆♥□○	●△◆♥□○	●△◆♥□○	▲◆□	▲◆□	▲◆□
Actina	●△◆♥□○	●△◆♥□○	●△◆♥□○	▲◆□	▲◆□	▲◆□
Canuk	●▲◆♥□○	●▲◆♥□○	●▲◆♥□○	▲◆□	▲◆□	▲◆□

● Abete R12 V8 (A+B+C)    △ Bosso R12 V4 (A+B+C)    ▲ Jennet R10    ◆ Ebano R11 (A+B)    ♥ Lyrid R11 V6 (A+B+C)  
 ■ Milon R12    □ Palude R11 (A+B)    ○ Pesse R11 V4 (A+B+C)    \ Apo1 R13 (A+B+C)

## SHODFOOT SLIP RATING DEFINITIONS (DIN 51130)

	R9	6-10°	General circulation areas, reception areas, canteens, restaurants, stairs
	R10	10-19°	Toilets & washrooms
	R11	19-27°	Kitchens with up to 100 meals/day, serving counters for unpacked meat
	R12	27-35°	Food processing rooms, kitchens with over 100 meals/day, external ramps
	R13	> 35°	Slaughter house, fish processing rooms

## BAREFOOT SLIP RATING DEFINITIONS (DIN 51097)

	Class A	≥ 12°	Barefoot, but mainly dry aisles and walkways, dry changing areas
	Class B	≥ 18°	Shower rooms, pool surrounds, wet changing areas, disinfectant spray areas
	Class C	≥ 24°	Areas constantly underwater, inclined pool surrounds jacuzzis

# Anti Slip

## APPEARANCE

Anti Slip

## MATERIAL

Porcelain

## USAGE

Floors and Walls

## SHADE VARIATION


V1 - Uniform

## SPECIAL PIECES

More special pieces available.  
For more information contact our sales team.


## BATTISCOPIA

90x300, 90x400,  
100x200mm




## STEP TREADS

300x300mm




## SIT-ON SKIRTING

100x200mm




## COVE BASE

100x200mm




## SHOWER TRAY EDGING

118x118mm  
118x243mm



## A1 COVE S1

40x200mm



## A5 S5

25x200mm



## ISO 10545 RESULTS

### 2. DIMENSIONS AND SURFACE QUALITY

Conforms

### 3. WATER ABSORPTION

< 0.1%

### 4. FLEXURAL STRENGTH

45 N/mm<sup>2</sup>

### 6. DEEP ABRASION RESISTANCE

< 150mm<sup>3</sup>

### 8. LINEAR THERMAL EXPANSION

$6 \times 10^{-6}$  °C

### 9. THERMAL SHOCK RESISTANCE

Conforms

### 10. MOISTURE EXPANSION

Conforms

### 12. FROST RESISTANCE

Conforms

### 13. CHEMICAL RESISTANCE

Conforms

### 14. STAIN RESISTANCE

Conforms

### SLIP RESISTANCE (DIN 51130-51097)

R10 - R13 (A+B+C)  
Call for details.

## MANUFACTURER CERTIFICATIONS:



EPD: Available  
ISO 14001

For LEED, BREEAM and WELL information, please ask for details. On request tiles can be tested to PTV BS7976-2. HSE surface roughness and NCS Colour values are also available upon request.  
All sizes shown are nominal. Due to the printing process and differing screen values actual tile colours may vary. E&OE.  
© Solus Ceramics Limited 2023. 020a.