

Inspired by the rugged beauty of arctic Scandinavia, this range is made up of seven enigmatic colours that capture the diversity of natural stone. Featuring cloudy shades, evocative speckles and whimsical veins.





ABOVE Floor: 3PPK101



RIGHT Floor: 3PPK102





Nordic 3PPK101

										ı,			÷	
	300×600 8mm	300×600 11mm	600×600 8mm	600×600 11mm	600×600 20mm	600×1200 8mm	600×1200 11mm	600×1200 20mm	750x750 8mm	750×1500 8mm	1000×1000 6mm	1000×1000 20mm	1000×1500 6mm	1000×300 6mm
Siberian	0	0	\bigcirc	0		0	0		0	0			1	
Basaltic	\Diamond	\Diamond \triangle	0	\Diamond \triangle		0	\bigcirc \triangle		0	0	1		1	
Narwhal	0	0	0	0		0	0		0	0				
Geyser	0	0 Δ	0	$\circ \triangle$		0	$\circ \triangle$		0	0			1	1
Walrus	\Diamond	0	0	0		0	0		0	0				
Kayak	\Diamond	0 Δ	0	$\circ \triangle$		0	\bigcirc \triangle	A	0	0	1	A	1	
Nordic	0	0	0	0		0	0		0	0			1	1

Noned R9

○ Honed R10

 \triangle Anti Slip R11 (A+B)

▲ Anti Slip R11 (A+B+C)

APPEARANCE

Limestone

MATERIAL

Porcelain

USAGE

Floors and Walls

SHADE VARIATION

V2 - Light

ISO 10545 RESULTS

2. DIMENSIONS AND SURFACE QUALITY

Conforms

10. MOISTURE EXPANSION

No rating

3. WATER ABSORPTION

0.08%

12. FROST RESISTANCE

Conforms

4. FLEXURAL STRENGTH

50 N/mm²

13. CHEMICAL RESISTANCE

Conforms

6. DEEP ABRASION RESISTANCE

140 mm³

14. STAIN RESISTANCE

Conforms

8. LINEAR THERMAL EXPANSION

7 MK-1

SLIP RESISTANCE (DIN 51130-51097)

Honed R9 Honed R10 Anti Slip R11 (A+B) Anti Slip R11 (A+B+C)

9. THERMAL SHOCK RESISTANCE

Conforms

MANUFACTURER CERTIFICATIONS:



ecovadis



EPD: Available ISO 14001

For LEED, BREEAM and WELL information, please ask for details. On request tiles can be tested to PTV BS7976-2. HSE surface roughness and NCS Colour values are also available upon request.

All sizes shown are nominal. Due to the printing process and differing screen values actual tile colours may vary. E&OE. © Solus Ceramics Limited 2024. 010.

> 40% Pre-consumer



EC1M 5RJ