

# Gritstone

4 COLOURS | 3 FINISHES | 7 SIZES



S  
O  
LUS

Floor:  
2VXT104



# Gristone

Gristone takes on the appearance of manually mixed, coarse grained concrete, complete with dynamic gritty clusters and randomly scattered pieces of gravel.



Floor:  
2VXT101





Doran  
2VXT101



Gortree  
2VXT104



Leode  
2VXT102



Cairnhill  
2VXT103



Floor:  
2VXT104

|           | 300x600<br>9mm | 600x600<br>9mm | 600x1200<br>9mm | 750x750<br>9mm | 750x1500<br>9mm | 900x900<br>20mm | 1200x1200<br>9mm |
|-----------|----------------|----------------|-----------------|----------------|-----------------|-----------------|------------------|
| Doran     | ● \            | ● \            | ● \             | ● \            | ● \             |                 | ● \              |
| Gortree   | ● \            | ● \            | ● \             | ● \            | ● \             |                 | ● \              |
| Leode     | ● \            | ● \            | ● \             | ● \            | ● \             | △               | ● \              |
| Cairnhill | ● \            | ● \            | ● \             | ● \            | ● \             |                 | ● \              |

● Matt R10   \ Soft   △ Out R11

## APPEARANCE

Concrete

## MATERIAL

Porcelain

## USAGE

Floors and Walls

## SHADE VARIATION

V3 - Moderate

## SPECIAL PIECES


Available in all colours.

For more information contact our sales team.

## BATTISCOPIA

70x600mm

70x750mm



## ISO 10545 RESULTS

### 2. DIMENSIONS AND SURFACE QUALITY

Conforms

### 3. WATER ABSORPTION

0.2%

### 4. FLEXURAL STRENGTH

Conforms

### 6. DEEP ABRASION RESISTANCE

Conforms

### 8. LINEAR THERMAL EXPANSION

7 MK<sup>-1</sup>

### 9. THERMAL SHOCK RESISTANCE

Conforms

### 10. MOISTURE EXPANSION

No rating

### 12. FROST RESISTANCE

Conforms

### 13. CHEMICAL RESISTANCE

Conforms

### 14. STAIN RESISTANCE

Class 5

### SLIP RESISTANCE (DIN 51130-51097)

Matt R10

Out R11

## MANUFACTURER CERTIFICATIONS:

**Declare.**

EPD: Available

ISO 14001

For LEED, BREEAM and WELL information, please ask for details. On request tiles can be tested to PTV BS7976-2. HSE surface roughness and NCS Colour values are also available upon request.

All sizes shown are nominal. Due to the printing process and differing screen values actual tile colours may vary. E&OE.  
© Solus Ceramics Limited 2023. 005b.

## BIRMINGHAM

Unit 1 Cole River Park  
Warwick Road B11 2QX

## LONDON

80 Clerkenwell Road  
EC1M 5RJ

## MANCHESTER

14 Kennedy Street  
M2 4BY

[solusceramics.com](http://solusceramics.com)

+44 (0)121 753 0777

[sales@solusceramics.com](mailto:sales@solusceramics.com)