

Porcelain Flare

10 COLOURS | 1 FINISH | 7 SIZES



S
O
S
L
U
S

Floor:
2SCT3081

Porcelain Flare

The extensive Porcelain Flare collection comes in a range of many colours. From deep greys to sumptuous pine to soft sand shades, these ever-popular tiles are synonymous with reliability and quality.



Floor:
2SCT3084
2SCT3083



Nebulosa *
2SCT3081



Scale
2SCT2047



Rostrata
2SCT2043



Ularia
2SCT3093



Sabella
2SCT2048



Nereis
2SCT3088



Actina *
2SCT3085



Pagarus
2SCT3084




















Canuk *
2SCT3086



Obelia
2SCT3083

SIZES AND FINISHES

	 125x250 8mm	 200x200 8mm	 200x200 12mm	 200x200 14mm	 300x300 8mm	 300x300 11.2mm	 300x300 14mm
 Nebulosa *		●	●	●	●	●	●
 Scale	●	●			●		
 Rostrata		●			●		
 Ularia		●			●		
 Sabella		●			●		
 Nereis		●			●		
 Actina *	●	●	●	●	●	●	●
 Pagarus		●			●		
 Canuk *		●	●	●	●	●	●
 Obelia		●			●		

● Matt R9

NOTES

* Selected colours are available in additional sizes in anti slip finishes, R10 - R13 (A+B+C).
Please see our Anti Slip range for details.

Porcelain Flare

APPEARANCE
Speckled

MATERIAL
Porcelain

USAGE
Floors and Walls

SHADE VARIATION
V1 - Uniform

SPECIAL PIECES
Available in all colours.
For more information contact our sales team.


BATTISCOPIA
90x300mm
100x200mm




LISTELLO
90x300mm



STEP TREADS
300x300mm



SIT-ON SKIRTING
100x200mm



A5 S5
25x200mm



ISO 10545 RESULTS

2. DIMENSIONS AND SURFACE QUALITY
Conforms

3. WATER ABSORPTION
 $\leq 0.1\%$

4. FLEXURAL STRENGTH
45-60 N/mm²

6. DEEP ABRASION RESISTANCE
Conforms

8. LINEAR THERMAL EXPANSION
 $6.3 \times 10^{-6} \text{ } ^\circ\text{C}$

9. THERMAL SHOCK RESISTANCE
No rating

10. MOISTURE EXPANSION
No rating

12. FROST RESISTANCE
Conforms

13. CHEMICAL RESISTANCE
Conforms

14. STAIN RESISTANCE
Conforms

SLIP RESISTANCE
(DIN 51130)
Matt R9

MANUFACTURER CERTIFICATIONS:



EPD: Available
ISO 14001

For LEED, BREEAM and WELL information, please ask for details. On request tiles can be tested to PTV BS7976-2. HSE surface roughness and NCS Colour values are also available upon request. All sizes shown are nominal. Due to the printing process and differing screen values actual tile colours may vary. E&OE. © Solus Ceramics Limited 2023. 015a.



up to 27%
Pre-consumer

**S
O
L
U
S**

BIRMINGHAM
Unit 1 Cole River Park
Warwick Road B11 2QX

LONDON
80 Clerkenwell Road
EC1M 5RJ

MANCHESTER
14 Kennedy Street
M2 4BY

solusceramics.com
+44 (0)121 753 0777
sales@solusceramics.com